Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the

Application.

Listing of Claims

1. (Currently Amended) A safety syringe and cap holding device comprising:

a syringe having a body portion and a needle assembly interconnected with the

body portion, the needle assembly including a needle with an injection end and a hub,

the hub including at least one recess disposed annularly about the hub;

a cover removably attached to the hub and covering the injection end of the needle,

the cover including at least a pair of opposing protrusions for engagement with the at least

one recess of the hub:

a cap holding device having a receptacle for receiving the cover; and

means in the cap holding device for disengaging the cover from the hub and

retaining the cover in the cap holding device to allow the syringe and needle assembly to

be withdrawn from the cap holding device with the injection end of the needle uncovered

while the cover remains in the cap holding device; and

means in the cap holding device for selectively retaining or releasing the cover from

engagement within the cap holding device.

-2-

Appln. No. 10/795,970 Amendment dated September 18, 2007 Reply to Office Action mailed June 18, 2007

2. (Canceled)

3. (Canceled)

4. (Previously Presented) The apparatus of claim 1, wherein the means for disengaging

the cover comprises a linkage system in the cap holding device for moving the at least pair

of opposing protrusions out of engagement with the at least one recess for disengaging the

cover from the hub.

5. (Previously Presented) The apparatus of claim 4, wherein the linkage system comprises

one or more hooks for engaging one or more handles on the cover for disengaging the at

least pair of opposing protrusions away from the at least one recess to disengage the cover

from the hub.

6. (Previously Presented) The apparatus of claim 4, wherein the linkage system is

actuated remotely from the cap holding device.

7. (Previously Presented) The apparatus of claim 4, wherein the means for disengaging the

cover comprises one or more solenoids in the cap holding device for moving one or more

hooks for engaging one or more handles on the cover for disengaging the at least pair of

opposing protrusions from the at least one recess to disengage the cover from the hub.

-3-

MEI 6720612v.1

Appln. No. 10/795,970

Amendment dated September 18, 2007

Reply to Office Action mailed June 18, 2007

8. (Previously Presented) The apparatus of claim 7, wherein the plurality of solenoids are

actuated remotely from the cap holding device.

9. (Canceled)

10. (Currently Amended) The apparatus of claim [[9]] 1, wherein the means for selectively

retaining or releasing the cover comprises a linkage system in the cap holding device for

engaging and disengaging a tip of the cover.

11. (Currently Amended) The apparatus of claim [[9]] 1, wherein the means for selectively

retaining or releasing the cover comprises one or more solenoids having one or more

hooks for engaging and disengaging the cap in the cap holding device.

12. (Currently Amended) The apparatus of claim [[9]] 1 wherein the cap holding device

comprises a weighted base.

13-21. (Canceled)

-4-

22. (Currently Amended) A safety syringe and cap holding device comprising:

a syringe having a body portion and a needle assembly interconnected with the

body portion, the needle assembly including a needle with an injection end and a hub;

a cover removably attached to the hub and covering the injection end of the needle,

the cover including one or more protrusions extending radially inward of the cover and one

or more handles corresponding to the one or more internally facing protrusions;

a cap holding device having a receptacle for receiving the cover; and

means in the cap holding device for disengaging the cover from the hub and

retaining the cover in the cap holding device to allow the syringe and needle assembly to

be withdrawn from the cap holding device with the injection end of the needle uncovered

while the cover remains in the cap holding device, the means for disengaging the cover

comprising one or more hooks in the receptacle for engaging the one or more handles to

move the one or more internally facing protrusions from the hub.

23. (Currently Amended) The apparatus of claim 22, wherein each of the one or more

hooks handles is substantially oval and includes an interior opening.

24. (Currently Amended) The apparatus of Claim 23, wherein the cover including includes

at least a pair of opposing handles.

-5-

Appln. No. 10/795,970

Amendment dated September 18, 2007

Reply to Office Action mailed June 18, 2007

25. (Previously Presented) The apparatus of Claim 22, wherein the one or more hooks is

sized to extend through the one or more handles.

26. (Previously Presented) A safety syringe and cap holding device comprising:

a syringe having a body portion and a needle assembly interconnected with the

body portion, the needle assembly including a needle with an injection end and a hub;

a cover removably attached to the hub and covering the injection end of the needle;

a cap holding device comprising a housing having a receptacle for receiving the

cover;

means in the cap holding device for disengaging the cover from the hub and

retaining the cover in the cap holding device to allow the syringe and needle assembly to

be withdrawn from the cap holding device with the injection end of the needle uncovered

while the cover remains in the cap holding device; and

an actuator positioned remotely from the housing for actuating the cap holding

device.

27. (Previously Presented) The apparatus of Claim 26, wherein the actuator is not

integrally attached to the housing.

-6-